

**High Performance  
Commercial Grade Specifications**



144/430 MHz  
DUAL BAND 5W  
FM TRANSCEIVER  
**FT-65**  
FT-65R: US and Asia  
FT-65E: Europe

144 MHz  
SINGLE BAND 5W  
FM TRANSCEIVER

**FT-25**

FT-25R: US and Asia  
FT-25E: Europe

FT-65/FT-25 Supplied Accessories  
(7.4V 1950mAh Li-ion battery SBR-25LI, Battery Charger SBH-22, AC Adapter SAD-20 and Belt Clip included)



- **Commercial Grade Specifications: IP54/MIL-STD 810 C, D and E**
- **1 Watt of Powerful, Clear Audio**
- **High Power 5 Watts Output and selectable setting 5W / 2.5W / 0.5W**
- **QRK (Four Quick Recall Key buttons: P1-P4) for Easy Operation**
- **Emergency Signaling, Bright white LED Flashlight, One-touch Alarm, and Quick HOME Channel Access**
- **Included 1950mAh Li-ion Battery Pack capable of over 17 hours of operation**
- **FM Broadcast Receiver Equipped**

**VALUABLE FEATURES FT-65/FT-25**

- 223 Memory Channels with 8-character alpha tags (222 Memory Channels for FT-25)
- Versatile Scanning Capabilities: VFO Scan, Memory Scan, Programmable memory scan (PMS), Memory bank scan, and Dual receive
- WX Channels with "Severe Weather" Alert (only available in NOAA weather service areas)
- VOX Operation with Optional VOX Earpiece Microphone (SSM-512B)
- 3.5-Hour Rapid Charger (SBH-22) Included
- PC Programmable with Optional Programming Cable (SCU-35)
- Transceiver-to-Transceiver Cloning with Optional Cloning Cable (SCU-36)
- ARTS (Automatic Range Transponder System) function
- DTMF Operation • CTCSS / DCS Operation
- Busy Channel Lock Out (BCL0)
- Battery Saver function • Automatic Power Off (APO)
- Transmitter Time Out Timer (TOT)



QRK (Quick Recall Key)

Battery Operating Time (Approximately)\*1

Band	SBR-25LI	SBR-26LI
144 MHz	17 hours	22 hours
430 MHz*2	16 hours	20 hours
FM Broadcast	11.5 hours	15 hours

Note: \*1 : (TX) 5; (RX) 5; Standby 90 Duty Cycle based on 5W TX Power  
\*2 : Only FT-65

**Ultimate Compact  
High Performance FM Handheld**



144/430MHz  
DUAL BAND 5W  
FM TRANSCEIVER  
**FT-4X**  
FT-4XR: US and Asia  
FT-4XE: Europe

144MHz  
SINGLE BAND 5W  
FM TRANSCEIVER

**FT-4V**

FT-4VR: US and Asia  
FT-4VE: Europe


FT-4X/FT-4V Supplied Accessories  
(7.4V 1750mAh Li-ion battery SBR-28LI, Battery Charger SBH-22, AC Adapter SAD-20 and Belt Clip included)



- **Ultimate Compact Design: W 2.1" x H 3.5" x D 1.2" (52 x 90 x 30 mm)**
- **1 Watt of Powerful, Clear Audio**
- **High Power 5 Watts Output and selectable setting 5W / 2.5W / 0.5W**
- **QRK (Two Quick Recall Keys: P1-P2) for Easy Operation**
- **Emergency Signaling, One-touch Alarm, and Quick HOME Channel Access**
- **Included 1750mAh Li-ion Battery Pack capable of over 15 hours of operation**
- **FM Broadcast Receiver Equipped**

**VALUABLE FEATURES FT-4X/FT-4V**

- 223 Memory Channels with 6-character alpha tags (222 Memory Channels for FT-4V)
- Versatile Scanning Capabilities: VFO Scan, Memory Scan, Programmable memory scan (PMS), Memory bank scan, and Dual receive
- WX Channels with "Severe Weather" Alert (only available in NOAA weather service areas)
- VOX Operation with Optional VOX Earpiece Microphone (SSM-512B)
- 3.5-Hour Rapid Charger (SBH-22) Included
- PC Programmable with Optional Programming Cable (SCU-35)
- Transceiver-to-Transceiver Cloning with Optional Cloning Cable (SCU-36)
- FM Broadcast Receiver Equipped
- ARTS (Automatic Range Transponder System) function
- DTMF Operation • CTCSS / DCS Operation
- Busy Channel Lock Out (BCL0)
- Battery Saver function • Automatic Power Off (APO)
- Transmitter Time Out Timer (TOT)



QRK (Quick Recall Key)

Battery Operating Time (Approximately)\*1

Band	SBR-28LI
144 MHz	15 hours
430 MHz*2	14 hours
FM Broadcast	12 hours

Note: \*1 : (TX) 5; (RX) 5; Standby 90 Duty Cycle based on 5W TX Power  
\*2 : Only FT-4X

	OPTIONS								
FT-65/FT-25	●	●	●	●	●	●	●	●	●
FT-4X/FT-4V	●	●			●	●	●	●	●

\*1 Depending on the transceiver version

